

Belshaw Adamatic

BX Convection Oven, 10-Tray

BX10-C, BX10-S

Features

- Produces an even bake
- Steam injection standard on all ovens
- 2 programmable controller options
 - Classic (9 programs) - BX4-C
 - Smartbake (99 programs) - BX4-S
- Compatible with 26" x 18" trays
- 'Cool to Touch' oven-doors
- ETL certified to UL-197 and NSF-4

Options

- Smartbake controller (standard on BX10-S model)



Top: BX10-S
(with Smartbake controller)



Bottom: BX10-C
(with Classic controller)



UL197

NSF STD 4

CLASSIC CONTROLLER (BX10-C)

Up to 9 programs. For each program, you control:

- Bake time
- Bake temperature
- Steam duration
- Damper open/shut
- Settings can be changed while the program is running.

Programs are set on control panel (no download from computer).

SmartBake Controller (BX10-S)

Holds up to 99 programs. Six phases possible in each program. For each phase, you control:

- Bake time
- Bake temperature
- Steam duration
- Fan cycles. Fan can reverse direction up to 9 times per bake program.
- Damper open/shut.
- Programs are set on control panel or via download from computer.
- The controller includes prominent countdown timer with audible signal at end of program.

Classic Controller



Standard interface

Smartbake Controller



Monitoring progress of bake

Easy-to-use screens

Fast menu choices

Model	BX10-S / BX10-C
Operation	
Shelves	4
Pan size	18" x 26"
Shelf spacing	3.5" (95 mm)
Dimensions	
Overall Width	34" (840 mm)
Overall Depth	53" (1350 mm)
Overall Height	74" (1870 mm)
Net weight	982 lbs (446 kg)
Shipping Class	85
Electrical	
Volts / Amps	208V-60-3 58 Amp 3+N+G
3-phase cord and plug (standard)	NEMA L21-30P, 4 ft (1.2m)
Water supply	30psi minimum
Damper	Butterfly type

