

Product Line	<b>CABINET PROOFER (Extra Depth)</b>
Model	EP18/24/34

## EP18/24/34 EXTRA-DEPTH PROOFER

### DESCRIPTION

Belshaw's EP18/24/34 extra-depth cabinet proofer is an expanded version of the EP18/24 proofer that accepts large donut screens 23" wide and 33" deep. It is compatible with Belshaw's extra-wide 634, 734CG, and 734FG open kettle fryers.

Designed for quality and convenience when proofing donuts, cinnamon rolls, and similar products, the EP18/24/34 is a robust mobile proofer that can be rolled into any convenient position for loading or unloading without missing a beat.

The EP18/24/34 also accepts standard donut screens 17 x 25" wide and 23" x 23". This makes it compatible with all Belshaw open kettle fryers (except 616B / Cut-N-Fry) and Donut Robot® Mark VI.

### STANDARD FEATURES

- Accepts donut screen sizes below
  - 17" x 25" (Belshaw 618L, 718LCG, 718LFG fryers)
  - 23" x 23" (Belshaw 624, 724CG, 724FG)
  - 23" x 33" (Belshaw 634, 734CG, 734FG)
  - OR any size in between the above
- 17 shelves with 3" shelf spacing when all 17 are used
- Capacity (at proofing time of 30 minutes)
  - **68** dozen donuts/hour when using **17" x 25" screens** holding 24 donuts each
  - **102** dozen donuts/hour when using **23" x 23" screens** holding 36 donuts each
  - **136** dozen donuts/hour when using **23" x 33" screens** holding 48 donuts each
- Six plexiglass doors enable the operator to put in or take out one or two screens, without opening a full height door
- Thermostat-controlled heat and humidity
- Blower system with ducts for circulating warm humid air
- 4 heavy duty casters (2 lockable)
- Self-contained electrical compartment that can be removed like a drawer
- Removable shelves
- Stainless steel construction
- No plumbing, hard wiring or special installation
- Water reservoir filled manually
- ETL and NSF4 certified

### OPTIONS

- 120V or 240V (single phase)
- Autowater with solenoid valve and garden hose connection to water supply



Serving bakeries for **95** years

Product Line	<b>CABINET PROOFER (Extra Depth)</b>
Model	EP18/24/34

**DIMENSIONS**

- Overall width: 28" (71cm)
- Overall depth: 42" (106cm)
- Overall height: 75" (190cm)
- Net weight: 302 lbs (137 kg)

**SHIPPING DATA**


Data is estimated, for North America shipments

- Carton size: 50" x 36" x 84"
- Carton weight: 500 lbs (227 kg)
- Freight Class: 100

**CERTIFICATIONS**




- North America standard models certified by ETL to UL-1889, NSF STD 4, and CSA C22.2
- CE models available for European Union and other countries



**ELECTRICAL OPTIONS**

- 120 Volts, 50/60 Hertz, 1 phase  
15 Amps, 1.8 Kilowatts  
Plug: NEMA 5-20P (N. America only), supplied standard.  
NOTE Not a standard 120V household plug, see at right .
- 208 Volts, 50/60 Hertz, 1 phase  
11.1 Amps, 2.3 Kilowatts  
Plug: 330P6W (N. America only) recommended, supplied by customer
- 240 Volts, 50/60 Hertz, 1 phase  
9.6 Amps, 2.3 Kilowatts  
Plug: 330P6W (N. America only) recommended, supplied by customer



**ACCESSORIES**

Item Nbr	Description
634-0013A	Donut proofing and frying screen for Belshaw 634, 734CG and 734FG fryers, 23" x 33"

Serving bakeries for **95** years